



1250Watt PowerReal EPS 12V Ver. 2.92 POWER SUPPLY



Feature:

- New Version 2.92 with Separated Six +12V rails**
 Independent 12V rails supply to MB/CPU and drives in order to provide stable and clean current to power-sensitive devices.
- 24 Pins Mainboard connector (Detachable 24 Pins, works with 20 & 24 Pins MB)**
 Support Intel Core i7, i5, Core 2 Quad, Core 2 Duo and AMD Phenom X4, X3, and Athlon 64 X2.
- 140mm Silent Cooling Fan**
 140mm Silent Cooling fan system provide maximum cooling for the power supply.
- SATA Ready**
 SATA Power connectors ready for SATA HDD and Drive connection. SATA connector x 8
- PCI Express VGA Connectors**
 Dedicated PCI Express VGA Connector for High Performance Interface VGA Card Extended Power.

Specification:

AC Input		115V ~ 240V 15A 50Hz / 60Hz		
1250W	Max Output Current Max Combined Wattage	DC Output	Min	Max
		+3.3V	1.0A	24A
		+5V	1.0A	30A
		+12V1	0.8A	20A
		+12V2	0.8A	20A
		+12V3	0.5A	20A
		+12V4	1.0A	35A
		+12V5	1.0A	35A
		+12V6	1.0A	20A
	-12V	0A	0.5A	
	+5VSB	0.1A	5.0A	
Cooling	140mm Silent Cooling Fan			
M.T.B.F.	100k+ hrs at 70% of full rated load			
Humidity	Operation : to 85%, relative humidity, non condensing at 25°C			
	Storage : to 95%, relative humidity, non condensing at 50°C			
Temperature	0 ~ 40°C (Operating)			
	-40 ~ 70°C (Storage)			
Dimension (LxWxH)	180mm x 150mm x 85mm			
Connectors	MB – 20+4 Pins x 1			
	12V – 8(4+4)+8 Pins x 1 (MainBoard)			
	12V/5V – 4Pins x 6 (Drives)			
	SATA – x 8			
	Floppy – 4 Pins x 1			
	PCI Express (VGA) – 6 pin x 2 – 6+2 pin x 2 (SLI Compatible)			



1250 Watt
ATX Power Supply

XION
PowerReal



3 way SLI Ready

up to 99.5% Active PFC

SATA Ready

MB Intel & AMD Connector Ready (24 Pins)

140mm Silent Cooling Led FAN

